



Architectural Nylon

Contents



Paris Series

273-279



Pull Handles and Accessories 281-

281-292

ARCHITECTURAL NYLON

The spindle is very easily introduced into

Introduce grub screw

Once fitted correctly this will achieve solid fixing

into hole. The grub screw point must locate into the slot in the spindle where it will bore a hole

the lever

Full Profile Spindle

Lever Handle

Spindle

HOPPE nylon levers and pull handles are manufactured to exacting standards from polyamide nylon giving good tensile properties, impact strength and wear resistance. nylon gives good antistatic behaviour and resistance to corrosion and chemicals.

HOPPE nylon levers are available in both solid and steel cored versions. The steel cored version being suitable for fire doors.

Spindles:

HOPPE Full Profile Spindle

HOPPE nylon levers are supplied with full profile spindles.

HOPPE full profile spindles have a tension spring running the full length of the spindle.

In screwing the lever handle grub screw into the slots in the middle of the spring, the tension spring expands achieving a secure fix to the lock follower.

Maintenance

HOPPE nylon furniture can be cleaned with water and or propriety detergents.

















Midnight (Dark) Blue LRV: 4.85

F7043 Flint (Dark) Grey LRV: 9,49



Black (Ebony)

F7506 Manhattan Grey LRV: 42.46

F8017 Brown (Sienna) LRV: 4.97







F9016

Diamond White LRV: 88.19



The Disability Discrimination Act - BS8300 - Document 'M'

The DDA is an Act of Parliament dealing with Human Rights Legislation, making it unlawful to discriminate against anyone on grounds of any disability whether permanent or temporary.

BS8300: 2001 "Design of buildings to meet the needs of disabled people – Code of Practice". This provides guidance on good practice in the design of buildings so that access is convenient for all.

Approved Document "M" (Doc M) of the building regulations (England and Wales), requires "that reasonable provision shall be made for people to gain access to and use the building and its facilities".

Lever Handles

Lever handles should be "of the return to door type". They do not have to be round bar. They should not have sharp edges or immediate changes of direction. They should be securely fixed to door by bolt through fixings and with minimum dimensions as stated in the diagram.

Pull Handles

Pull handles should be bolt fixed to door and have roses to aid the partially sighted. Minimum dimensions are stated in the following diagram. The upper fixing should be a minimum of 1400mm above floor level. Pull handles can be longer but not shorter than these dimensions.

Kick Plates


To prevent damage to doors from wheelchairs, kick plates should be at least 400mm high.

Tonal Contrast

To assist the partially sighted, door furniture should contrast with the door, by a minimum of 20 points. This so called "light reflectance value" is measured on a scale of 0 to 100 with pure black being 0 and pure white 100. Hardware and door manufacturers should be able to give the value (from 0 to 100) of their products.

Cold to the touch

External handles should not be cold to the touch. Nylon, wooded and powder coated handles or handrails will satisfy this, but not metal versions.




Architectural Nylon



Paris Series







Solid Nylon Lever on Round Rose (unsprung) Ø 21mm

features

- Supplied with wood screw fixings
- Supplied with 8mm x 105mm full profile spindle (630905)
- Suitable for 38mm to 47mm door thickness
- NOT to be used on Fire Doors
- Suitable for use with ARRONE Plus escape locks

standards and certification

Conformity Statement: Meets the dimensional recommendations of BS8300 and Approved Document "M"

ID NO	PRODUCT REF	DESCRIPTION	
	AR600/10	Lever on round rose – Comprising AR600L lever and AR600R rose	
572809	AR600/10/20	Spring cassette for above (single)	



ø21

140

38

_____0

65

Steel Cored Lever on Round Rose (unsprung) Ø 21mm

features

- Supplied with wood screw fixings
- Supplied with 8mm x 105mm full profile spindle (630905)
- Suitable for 38mm to 47mm door thickness
- Suitable for use on Fire Doors
- Suitable for use with ARRONE Plus escape locks

standards and certification



Conformity Statement: Meets the dimensional recommendations of BS8300 and Approved Document "M"

ID NO	PRODUCT REF	DESCRIPTION
	AR600/20	Lever on round rose – Comprising AR600SCL steel cored lever and AR600R rose
572809	AR600/10/20	Spring cassette for above (single)



Solid Nylon Lever on Radius Plate (unsprung) Ø 21mm


features

- Supplied with wood screw fixings
- Supplied with 8mm x 105mm full profile spindle (630905)
- Suitable for 38mm to 47mm door thickness
- NOT to be used on Fire Doors

standards and certification

ይ Conformity Statement: Meets the dimensional recommendations of BS8300 and Approved Document "M"







ID NO	PRODUCT REF	DESCRIPTION
	AR600/11	Long plate latch furniture (AR600PLA plate and AR600L Lever)
	AR600/12	Lock furniture (AR600PLO plate and AR600L Lever)
	AR600/13	Euro profile lock furniture 47.6mm centres (AR600PP plate and AR600L Lever)
	AR600/13-72	Euro profile lock furniture 72mm centres (AR600PP-72 plate and AR600L Lever)
	AR600/14	Oval profile lock furniture 48.5mm centres (AR600PO plate and AR600L Lever)
	AR600/15	Bathroom furniture 57mm centres (AR600PB plate and AR600L Lever)
	AR600/15-78	Bathroom furniture 78mm centres (AR600PB-78 plate and AR600L Lever)

(

R

EURO








BATHROOM

ê

57 78





Steel Cored Lever on Radius Plate (unsprung) Ø 21mm

features


- Supplied with wood screw fixings
- Supplied with 8mm x 105mm full profile spindle (630905)
- Suitable for 38mm to 47mm door thickness
- Suitable for use on Fire Doors

standards and certification

ጜ

Conformity Statement: Meets the dimensional recommendations of BS8300 and Approved Document "M"

ID NO	PRODUCT REF	DESCRIPTION
	AR600/21	Long plate latch furniture (AR600PLA plate and AR600SCL Lever)
	AR600/22	Lock furniture (AR600PLO plate and AR600SCL Lever)
	AR600/23	Euro profile lock furniture 47.6mm centres (AR600PP plate and AR600SCL Lever)
	AR600/23-72	Euro profile lock furniture 72mm centres (AR600PP-72 plate and AR600SCL Lever)
	AR600/24	Oval profile lock furniture 48.5mm centres (AR600PO plate and AR600SCL Lever)
	AR600/25	Bathroom furniture 57mm centres (AR600PB plate and AR600SCL Lever)
	AR600/25-78	Bathroom furniture 78mm centres (AR600PB-78 plate and AR600SCL Lever)





Solid Nylon Levers on Rectangular Plate (unsprung) Ø 21mm


features

- Supplied with wood screw fixings
- Supplied with 8mm x 105mm full profile spindle (630905)
- Suitable for 38mm to 47mm door thickness
- NOT to be used on Fire Doors

standards and certification

Conformity Statement: Meets the dimensional recommendations of BS8300 and Approved Document "M"






ID NO	PRODUCT REF	DESCRIPTION
	AR600/31	Long plate latch furniture (AR6/11 plate and AR600L Lever)
	AR600/32	Lock furniture (AR6/12 plate and AR600L Lever)
	AR600/33	Euro profile lock furniture 47.6mm centres (AR6/13 plate and AR600L Lever)
	AR600/33-72	Euro profile lock furniture 72mm centres (AR6/13-72 plate and AR600L Lever)
	AR600/34	Oval profile lock furniture 48.5mm centres AR6/14 plate and AR600L Lever)
	AR600/35	Bathroom furniture 57mm centres (AR6/15 plate and AR600L Lever)
	AR600/35-78	Bathroom furniture 78mm centres (AR6/15-78 plate and AR600L Lever)


(

 \bigcap

EURO










BATHROOM





Steel Cored Levers on Rectangular Plate (unsprung) Ø 21mm

features

- Supplied with wood screw fixings
- Supplied with 8mm x 105mm full profile spindle (630905)
- Suitable for 38mm to 47mm door thickness
- Suitable for use on Fire Doors

standards and certification

ይ

Conformity Statement: Meets the dimensional recommendations of BS8300 and Approved Document "M"

ID NO	PRODUCT REF	DESCRIPTION
	AR600/41	Long plate latch furniture (AR6/11 plate and AR600SCL Lever)
	AR600/42	Lock furniture (AR6/12 plate and AR600SCL Lever)
	AR600/43	Euro profile lock furniture 47.6mm centres (AR6/13 plate and AR600SCL Lever)
	AR600/43-72	Euro profile lock furniture 72mm centres (AR6/13-72 plate and AR600SCL Lever)
	AR600/44	Oval profile lock furniture 48.5mm centres (AR6/14 plate and AR600SCL Lever)
	AR600/45	Bathroom furniture 57mm centres (AR6/15 plate and AR600SCL Lever)
	AR600/45-78	Bathroom furniture 78mm centres (AR6/15-78 plate)

48 ()()47.6 72 48.5 57 78 155 57 ê \bigcirc Ŷ 9 46 LATCH LEVER KEY EURO OVAL BATHROOM



HOPPE Escutcheons, Indicator & Turn – K15S

52

38

BLANK

8

Escutcheon (8mm)

features

• Ø 52mm with 38mm fixing centres

ID NO	PRODUCT REF	DESCRIPTION
	AR600/26	Lever key escutcheon (pair)
	AR600/27	Euro profile escutcheon (pair)
	AR600/28	Oval profile escutcheon (pair)
	AR600/30	Blank escutcheon (pair)

+

38

OVAL





Bathroom Indicator & Turns (8mm Rose)

38

EURO

features

• 5mm Spindle


38


LEVER KEY

• Disabled bathroom turn is colour coated aluminium

ID NO	PRODUCT REF	DESCRIPTION
	AR600/29	Bathroom turn and indicator
	AR600/29D-H	Disabled Bathroom turn and indicator

1515527 **AR-6/7/8-SLEEVE** Spindle sleeve pack – converts 5m spindle to either 6, 7 or 8mm









2

Pull Handles and Accessories



Steel Cored Straight Pull Handles ('D' Handles) Ø 23mm Concealed Screw Fixing – HOPPE Ref. K5050

features

Suitable for 40mm to 50mm door thickness

	AR602/165CF	165mm centres, pull handle
ID NO	PRODUCT REF	DESCRIPTION

Steel Cored Straight Pull Handles ('D' Handles) Ø 34mm Concealed Screw Fixing – HOPPE Ref. K5030


features

• Suitable for 40mm to 50mm door thickness

standards and certification

Conformity Statement: Pull Handles with a length of 400mm and above meet the dimensional recommendations of BS8300 and Approved Document "M"

ID NO	PRODUCT REF	DESCRIPTION
	AR602/220CF	220mm centres, pull handle
	AR602/300CF	300mm centres, pull handle
	AR602/425CF	425mm centres, pull handle
	AR602/600CF	600mm centres, pull handle





ø34

ø34

ø23

ø23

165

Steel Cored Straight Pull Handles ('D' Handles) Ø 23mm Bolt Through Fixing– HOPPE Ref. K5050

features

- Suitable for 40mm to 50mm door thickness
- Supplied with bolt through fixing 793860 and matching bolt cover caps

ID NO	PRODUCT REF	DESCRIPTION
	AR602/165BF	165mm centres, pull handle

Steel Cored Straight Pull Handles ('D' Handles) Ø 34mm Bolt Through Fixing – HOPPE Ref. K5030

features

- Suitable for 40mm to 50mm door thickness
- Supplied with two bolt through fixings (8539158) and matching bolt cover caps

standards and certification



Conformity Statement: Pull Handles with a length of 400mr	n and above meet
the dimensional recommendations of BS8300 and Approved	d Document "M"

ID NO	PRODUCT REF	DESCRIPTION
	AR602/220BF	220mm centres, pull handle
	AR602/300BF	300mm centres, pull handle
	AR602/425BF	425mm centres, pull handle
	AR602/600BF	600mm centres, pull handle

Steel Cored Straight Pull Handles ('D' Handles) Ø 34mm Back-to-Back Fixing – HOPPE Ref. K5030

features

- Suitable for 40mm to 50mm door thickness
- Supplied with back-to-back fixing (592302)
- Supplied with inner pull handle drilled, with grub screws to lock back-toback fixing


standards and certification




Conformity Statement: Pull Handles with a length of 400mm and above meet the dimensional recommendations of BS8300 and Approved Document "M"

ID NO	PRODUCT REF	DESCRIPTION
	AR602/220BB	220mm centres, pull handle
	AR602/300BB	300mm centres, pull handle
	AR602/425BB	425mm centres, pull handle
	AR602/600BB	600mm centres, pull handle














Steel Cored Cranked Pull Handles Ø 34mm Concealed Screw Fixing – HOPPE Ref. K5130

features

• Suitable for 40mm to 50mm door thickness

ID NO	PRODUCT REF	DESCRIPTION
	AR603/200CF	200mm centres, pull handle
	AR603/300CF	300mm centres, pull handle

Steel Cored Cranked Pull Handles Ø 34mm Bolt Through Fixing – HOPPE Ref. K5130

- Suitable for 40mm to 50mm door thickness
- Supplied with two bolt through fixings (8539158) and matching bolt cover caps

ID NO	PRODUCT REF	DESCRIPTION
	AR603/200BF	200mm centres, pull handle
	AR603/300BF	300mm centres, pull handle




Steel Cored Cranked Pull Handles Ø 34mm Back-to-Back Fixing – HOPPE Ref. K5130

- Suitable for 40mm to 50mm door thickness
- Supplied with back-to-back fixing (592302)
- Supplied with inner pull handle drilled, with grub screws to lock back-toback fixing

ID NO	PRODUCT REF	DESCRIPTION
	AR603/200BB	200mm centres, pull handle
	AR603/300BB	300mm centres, pull handle







300


Steel Cored "V" Shaped Pull Handles Ø 34mm Bolt Through Fixing – HOPPE Ref. K5230

features

- Suitable for 40mm to 50mm door thickness
- Supplied with two bolt through fixings (8539158) and matching bolt cover caps

ID NO	PRODUCT REF	DESCRIPTION	
	AR604/300BF	300mm centres, pull handle	





Steel Cored "V" Shaped Pull Handles Ø 34mm Back-to-Back Fixing – HOPPE Ref. K5230

- Suitable for 40mm to 50mm door thickness
- Supplied with back-to-back fixing (592302)
- Supplied with one inner pull handle drilled, with grub screws to lock back-toback fixing

ID NO	PRODUCT REF	DESCRIPTION
	AR604/300BB	300mm centres, pull handle




Steel Cored Semi-Circular Pull Handles Ø 34mm Bolt Through Fixing – HOPPE Ref. K5330

features

- Suitable for 40mm to 50mm door thickness
- Supplied with bolt through fixing set (618668) and matching bolt cover caps
- Supplied with pull handle drilled, with grub screws

ID NO	PRODUCT REF	300mm centres, pull handle
	AR000/3000F	300mm centres, puir nancie






Steel Cored Semi-Circular Pull Handles Ø 34mm Back-to-Back Fixing – HOPPE Ref. K5330

- Suitable for 40mm to 50mm door thickness
- Supplied with two back-to-back fixings (600168)
- Supplied with both pull handles drilled, with grub screws to lock back-to-back fixing

ID NO	PRODUCT REF	DESCRIPTION
	AR605/300BB	300mm centres, pull handle





Pull Handles and Accessories

HOPPE Accessories

-			
	ID NO	PRODUCT REF	DESCRIPTION
		AR607IM	80mm x 150mm concealed fixing, international male sign
		AR607IF	80mm x 150mm concealed fixing, international female sign
		AR607ID	80mm x 150mm concealed fixing, international disabled sign
	ID NO	PRODUCT REF	DESCRIPTION
		AR612	Ø 32mm floor/wall mounted door stop 20mm projection
and a second sec		AR613	Ø 52mm floor/wall mounted door stop 40mm projection
	ID NO	PRODUCT REF	DESCRIPTION
and the second		AR615	Ø 52mm bell push
	ID NO	PRODUCT REF	DESCRIPTION
		AR617A	Face fixing hat and coat hook (20mm wide)
(AR617B	Concealed fixing hat and coat hook (20mm wide)
		AR618	Face fixing coat hook (20mm wide)
		AR619	Concealed fixing coat hook (20mm wide)
		Anois	Concealed fixing coat hook (201111 wide)
	ID NO	PRODUCT REF	DESCRIPTION
		AR620	Ø 20mm toilet roll holder
		AR620PP	Ø 20mm locking toilet roll holder
	631810	AR620PP-KEY	Key for AR620PP
	ID NO	PRODUCT REF	DESCRIPTION
		AR626	160mm x 220mm towel ring
	ID NO	PRODUCT REF	DESCRIPTION
1		AR621	Ø 40mm cupboard knob – 40mm projection
	ID NO	PRODUCT REF	DESCRIPTION
		AR622A	10mm x 64mm screw fixing from back, cabinet handle 32mm projection
		AR622B	12mm x 96mm screw fixing from back, cabinet handle 38mm projection

AR622C

20mm x 128mm screw fixing from back, cabinet handle

55mm projection



★ 🚯

ARRONE® Nylon Accessories

ID NO	PRODUCT REF	DESCRIPTION
	AR607M	100mm x 150mm rectangular male sign
	AR607F	100mm x 150mm rectangular female sign
AR607D 100mm x 150mm rectangular disabled sign		100mm x 150mm rectangular disabled sign

ID NO	PRODUCT REF	DESCRIPTION	
	AR624A	75mm x 305mm square end, self adhesive finger plate	
	AR624B	75mm x 305mm radiused end, self adhesive finger plate	

ID NO	PRODUCT REF	DESCRIPTION		
	AR625	Self adhesive kicking plate - Cut to order	And in case of the local division of the loc	

ARRONE® Colour Coated Accessories

ID NO	PRODUCT REF	DESCRIPTION
	AR606S	Cylinder pull for standard rim cylinder
	AR606YP	Cylinder pull for euro profile cylinder
	AR606U	Cylinder pull for oval profile cylinder
ID NO	PRODUCT REF	DESCRIPTION
	AR610A	150mm surface door bolt
	AR610B	200mm surface door bolt
ID NO	PRODUCT REF	DESCRIPTION
	AR610C	19mm x 200mm lever action flush bolt
ID NO	PRODUCT REF	DESCRIPTION
	AR614	Wall mounted door stop – 75mm projection
ID NO	PRODUCT REF	DESCRIPTION
	AR628A	75mm x 50mm x 1.75mm Colour coated steel butt hinge with matching screws (1838 type) (See Hinges section)
	AR628B	100mm x 75mm x 2.25mm Colour coated steel butt hinge with matching screws (1838 type) (See Hinges section)
	AR628C	75mm x 63mm x 2.75mm Colour coated steel butt hinge with matching screws (451 type) (See Hinges section)
	AR628D	100mm x 75mm x 2.75mm Colour coated steel butt hinge with matching screws (451 type) (See Hinges section)
	ID NO	AR606S AR606YP AR606U DNO PRODUCT REF AR610A AR610B DNO PRODUCT REF AR610C DNO PRODUCT REF AR614 DNO PRODUCT REF AR614 AR628A AR628B AR628B



Bathroom Hardware for Inclusive Design

AR763 Folding Grab Rail

features

• Also available in Stainless Steel: see Stainless Steel section

ID NO	PRODUCT REF	DESCRIPTION
8510234	AR763-WH	Folding grab rail

AR764 Backrest

features

• Also available in Stainless Steel: see Stainless Steel section

ID NO	PRODUCT REF	DESCRIPTION
8510248	AR764-WH	Back rest

AR765 Grab/Towel Rail Ø 34mm x 600mm

features

• Also available in Stainless Steel: see Stainless Steel section

ID NO	PRODUCT REF	DESCRIPTION
87107697	AR765-WH	Ø 34mm X 600mm Grab/towel rail

"DOC-M" Packs

features

• Also available in Stainless Steel: see Stainless Steel section

ID NO	PRODUCT REF	DESCRIPTION
87103089	AR767-WH	Doc "M" Pack including 1no AR763, 1 No AR764 & 3 no AR765
87108583	AR768-WH	Doc "M" Pack including 1no AR763, 1 No AR764 & 4 no AR765









HOPPE Nylon Series Spares and Fixings

Spindles

ID NO	PRODUCT REF	DESCRIPTION
630905	06855-0105-0000	8mm x 105mm full profile spindle to suit up to 44mm door thickness
680092	06855-2589-0000	8mm x 125mm full profile spindle to suit up to 54mm door thickness
821914	06855-2590-0000	8mm x 135mm full profile spindle to suit up to 64mm door thickness
630929	07050-1789-0000	5mm x 75mm solid spindle for bathroom furniture upto 50mm thick door

Screws

ID	NO	PRODUCT REF	DESCRIPTION
63	30912	AR-GRUB-FULL-SAA	Spare grub screw to suit full profile spindle
70)1742	AR200FP	Furniture fixing pack comprising 2 male/female bolt fixings and 4 wood screws

Pull Handle Fixings

ID NO	PRODUCT REF	DESCRIPTION
8539158	AR602BF	Single M12 x 90mm bolt – for bolt fixing Ø 34mm pull handles – AR602, 603 & 604
618668	ARBF-25/30	Pair bolts for bolt fixing Ø 34mm pull handles – AR605
592302	AR602BB	Pair back to back fixings for Ø 34mm pull handles – AR602, 603 & 604, door thickness 40-50mm
1743332	ARBB-3	Pair back to back fixings for Ø 34mm pull handles – AR602, 603 & 604, door thickness 50-60mm
600168	ARBB-25/30-44	Single back to back fixing for \emptyset 34mm pull handles AR605
600595	07810-5200-0012	Back to back fixings for glass doors (8-13mm) Ø 34mm pull handles AR602, 603 & 604
573585	ARBB-25/30-8/13	Back to back fixings for glass doors (8-13mm) Ø 34mm pull handles AR605